

RESPONSIBILITY OF VENDOR)

W8x24 STEEL BEAM SPACE STEEL POSTS EXCEED 12'-0" SPAN C.C.- NOTCH FLOOR TRUSS 9" DEPTH X 12" WIDE FOR BEAM

8" x 8'-0" FOX BLOCK INSULATED FORM BASEMENT WALLS R23 FILLED WITH POURED CONCRETE ON A 16" x 8" POURED CONCRETE FOOTING W/ 2 EA #4 ROUND BAR CONTINUOUS WITH 4" DRAINTILE INSIDE AND OUTSIDE THE FOOTING

4" POURED CONCRETE BASEMENT FLOOR ON A COMPACTED SAND LIFT

THICKEN FLOOR 2' x 2' x 10" THICK UNDER POSTS AS SHOWN

# FOX BLOCK INSULATING CONCRETE FORMS

SCALE: 3/4" = 1'-0"

11-1/4" x 8'-0" RHINO BLOCK INSULATING CONCRETE FORM BASEMENT WALLS FILLED WITH 7" THICK POURED CONCRETE ON A 20" x 10" POURED CONCRETE FOOTING W/ 2 EA #4 ROUND BAR CONTINUOUS WITH 4" DRAINTILE INSIDE AND OUTSIDE THE FOOTING

4" POURED CONCRETE BASEMENT FLOOR W/ IN FLOOR HEAT TUBING ON A STONE LIFT

13" THICK THERMOFORM VERTICAL INSULATED CONCRETE FORM WALLS FILLED WITH 8" THICK POURED CONCRETE ON A 24" x 12" POURED CONCRETE FOOTING W/ 2 EA #4 ROUND BAR CONTINUOUS AND 4" DRAINTILE INSIDE AND OUTSIDE THE FOOTING

# RHINO BLOCK INSULATING CONCRETE FORMS

SCALE: 3/4" = 1'-0"

# THERMOFORM VERTICAL INSULATED CONCRETE FORM

SCALE: 3/4" = 1'-0"

SCALE: Noted  
DATE: 1/21/13  
NAME: BL  
DWG. NO.: 0  
CAD FILE: InsulatedConcreteForms21Jan13  
REVISIONS: 18JAN17

INSULATED CONCRETE FORM SECTIONS

**BESTIMATE LLC**  
http://bestimatellc.com  
714 E Ninth St  
Marshfield, WI 54449  
bob@bestimatellc.com  
715-506-0040



PAGE NO: